

LED LAMP SPECIFICATION COMPARISON AND LINKS
TO ONLINE CUT SHEETS AND TECHNICAL DOCUMENTS
JUNE 2017



FIND AND COMPARE LAMP SOLUTIONS IN THIS DIRECTORY:

GET MORE INFORMATION ONLINE:

CFL / PL-L	Pin-Based	Types A and B	p. 3	https://www.lunera.com/cfl-led-lamps
T8 (T12) Linear		Type A	p. 4	https://www.lunera.com/lunera-tled-lamps
T8 (T12) Linear	Single-Ended	Type B	p. 5	https://www.lunera.com/lunera-tled-lamps
T8 (T12) Linear	Double-Ended	Type B	p. 6	https://www.lunera.com/lunera-tled-lamps
T8 U-Bend		Types A and B	p. 7	https://www.lunera.com/lunera-tled-lamps
T5HO (T5) Linear	External Driver	Type A	p. 8	https://www.lunera.com/lunera-tled-lamps
T8 / T5HO Retrofit Kits	External Driver	Type C	p. 9	https://www.lunera.com/lunera-led-retrofit-kits
Metal Halide and High Pressure Sodium	Vertical Mount	Type A	p. 10	https://www.lunera.com/hid-led-lamps
Metal Halide and High Pressure Sodium	Vertical Mount	Type B	p. 11	https://www.lunera.com/hid-led-lamps
Metal Halide or High Pressure Sodium (No-Fan)	Vertical Mount	Type A	p. 12	https://www.lunera.com/hid-led-lamps
Metal Halide or High Pressure Sodium	Horizontal Mount	Type A	p. 13	https://www.lunera.com/hid-led-lamps
Metal Halide and High Pressure Sodium	Post Top (360)	Types A and B	p. 14	https://www.lunera.com/hid-led-lamps
Metal Halide and High Pressure Sodium Retrofit Kit		Type B	p. 15	https://www.lunera.com/products/lunera-mh-led-lamps

Type A = Ballast Driven (plug-and-play)

Type B = Ballast Bypassed

Type C = External LED Driver

All lamps have applicable UL, FCC, and RoHS compliance.

RESOURCES:

Country/State Directory of Lunera Offices and Agents

<https://www.lunera.com/find-office-agent>

Locate a Distributor or Online Retailer

<https://www.lunera.com/buy>

Contact Lunera

<https://www.lunera.com/contact>

Lunera Technical Support

<http://bit.ly/luneratechsupport>

Turnkey Lighting as a Service

<https://www.lunera.com/lighting-as-a-service>

CFL / PLL REPLACEMENT LAMPS

Ballast Driven and Type B: Ballast Bypassed

Type A:

[<< BACK TO TOP](#)









[Click title for Cut Sheet and more >>](#)

Lunera CFL LED G24q

Lunera CFL LED G24d

Lunera CFL LED GX23

Lunera PLL LED 2G11

		Lunera CFL LED G24q		Lunera CFL LED G24d		Lunera CFL LED GX23		Lunera PLL LED 2G11	
Replaces	Equivalent Lamp Type	CFL		CFL		CFL		PLL	
	Socket	4-Pin G24q		2-Pin G24d		2-pin GX23		4-Pin 2G11	
	Equivalent Wattage	42/32/26/18W		26/18W		13W		55/40/36W	
	Dimmable	Contact Lunera for Dimmer Compatibility		Contact Lunera for Dimmer Compatibility		Contact Lunera for Dimmer Compatibility		Contact Lunera for Dimmer Compatibility	
Energy	Power Source	Type A Ballast Driven		Type A Ballast Driven		Type A Ballast Driven		Type B Ballast Bypassed	
	Lamp Wattage (W)	11W		13W		5W		22W	
Light	Lamp Max Lumens (lm)	1,350	1,445	950	1,000	580	580	2,600	2,600
	CCT (K)	2700 / 3000 / 3500 / 4000		2700 / 3000 / 3500 / 4000		2700 / 3000 / 3500 / 4000		2700 / 3000 / 3500 / 4000	
	Light Source	LED		LED		LED		LED	
	Lamp Mount / Light Direction	Vertical	Horizontal	Vertical	Horizontal	Vertical or Horizontal		Vertical or Horizontal	
									
Physical	Height (in.)	5.17	4.53	5.17	4.53	6.01	6.01	22.4	22.4
	Width (in.)	1.38	2.36	1.38	2.36	1.28	1.28	1.71	1.71
	Depth (in.)	1.38	2.01	1.38	2.01	0.82	0.82	0.68	0.68
	Weight (lbs.)	0.25	0.25	0.25	0.25	0.10	0.10	0.35	0.35
Features	DLC Listed	Yes, DLC 4.2		No Category		No Category		No Category	
	Thermal Fuse Protection	Yes		No		No		No	
	Integrated Sensors <small>* If yes, verify availability on cut sheet.</small>	No		No		No		No	

T8 (T12) LINEAR REPLACEMENT LAMPS

Ballast Driven

Type A:

LUNERA®

[<< BACK TO TOP](#)

[Click title for Cut Sheet and more >>](#)

Lunera T8 LED 2FT

Lunera T8 LED 3FT








Lunera T8 LED 4FT

Lunera T8 LED 8FT

Lunera T12 LED 8FT

Replaces	Equivalent Lamp Type	T8 Linear	T8 Linear	T8 Linear	T8 Linear	T8 Linear	T12 Linear (using T8 lamp / ballast)	T12 Linear (using T8 lamp / ballast)
	Equivalent Wattage	20/17/15W	30/25/21W	32/30/28/25W	75/60/59/54W	75/60/59/54W	75/60/59/54W	75/60/59/54W
	Socket	Bi-Pin G13	Bi-Pin G13	Bi-Pin G13	Double Recessed Contact R17d	Single Pin Fa8	Double Recessed Contact R17d	Single Pin Fa8
	Dimmable	Contact Lunera for Dimmer Compatibility	Contact Lunera for Dimmer Compatibility	Contact Lunera for Dimmer Compatibility	Contact Lunera for Dimmer Compatibility	Contact Lunera for Dimmer Compatibility	Contact Lunera for Dimmer Compatibility	Contact Lunera for Dimmer Compatibility

Energy	Power Source	Type A: Ballast Driven (Instant/Rapid/Programmed)	Type A: Ballast Driven (Instant/Rapid/Programmed)	Type A: Ballast Driven (Instant/Rapid/Programmed)	Type A: Ballast Driven (Instant/Rapid/Programmed)	Type A: Ballast Driven (Instant-Start)	Type A: Ballast Driven (Instant/Rapid/Programmed)	Type A: Ballast Driven (Instant-Start)
	Socket Wiring	Shunted or Un-Shunted Tombstone	Shunted or Un-Shunted Tombstone	Shunted or Un-Shunted Tombstone	Shunted or Un-Shunted Tombstone	Shunted or Un-Shunted Tombstone	Shunted or Un-Shunted Tombstone	Shunted or Un-Shunted Tombstone
	Lamp Wattage (W)	8W	11W	11W 15W	42W	24W 33W	42W	24W 33W

Light	Lamp Max Lumens (lm)	1,200	1,400	1,800 2,200	5,500	3,500 4,400	5,500	3,500 4,400
	CCT (K)	3000 / 3500 / 4000 / 5000	3000 / 3500 / 4000 / 5000	3000 / 3500 / 4000 / 5000	3000 / 3500 / 4000 / 5000	3000 / 3500 / 4000 / 5000	3000 / 3500 / 4000 / 5000	3000 / 3500 / 4000 / 5000
	Light Source	LED	LED	LED	LED	LED	LED	LED
	Tube Length	2FT 	3FT 	4FT 	8FT 	8FT 	8FT 	8FT 
	Beam Angle / Beam Spread	230° / 330°	230° / 330°	230° / 330°	230° / 330°	230° / 330°	230° / 330°	230° / 330°

Physical	Tube Material	Glass with Toughened Ends	Glass with Toughened Ends	Glass with Toughened Ends	Glass with Toughened Ends	Glass with Toughened Ends	Glass with Toughened Ends	Glass with Toughened Ends
	Length (in.)	23.7	35.75	47.72	93.74	93.74	93.74	93.74
	Diameter (in.)	1.00	1.00	1.00	0.94	0.94	0.94	0.94
	Width (in.)	---	---	---	---	---	---	---
	Weight (lbs.)	0.25	0.35	0.45	0.90	0.90	0.90	0.90

Features	DLC Listed	Yes, DLC 4.2	No Category	Yes, DLC 4.2	No Category	No Category	No Category	No Category
	Thermal Fuse Protection	Yes	Yes	Yes	Yes	Yes	Yes	Yes
	P.E.T. Shatter Guard Glass	Yes, Option	Yes, Option	Yes, Option	Yes, Included	Yes, Included	Yes, Included	Yes, Included
	Integrated Sensors	No	No	No	No	No	No	No

* If yes, verify availability on cut sheet.

T8 (T12) LINEAR REPLACEMENT LAMPS

Type B: Single-Ended Ballast Bypassed

[Click title for Cut Sheet and more >>](#)

Lunera T8 LED 2FT

Lunera T8 LED 3FT

Lunera T8 LED 4FT

Lunera T8 LED 8FT

Lunera T12 LED 8FT

Replaces	Equivalent Lamp Type	T8 Linear	T8 Linear	T8 Linear	T8 Linear	T12 Linear (using T8 lamp / ballast)	
	Equivalent Wattage	20/17/15W	30/25/21W	32/30/28/25W	75/60/59/54W	75/60/59/54W	
	Socket	Bi-Pin G13	Bi-Pin G13	Bi-Pin G13	Single Pin Fa8	Single Pin Fa8	
	Dimmable	Contact Lunera for Dimmer Compatibility	Contact Lunera for Dimmer Compatibility	Contact Lunera for Dimmer Compatibility	Contact Lunera for Dimmer Compatibility	Contact Lunera for Dimmer Compatibility	

Energy	Power Source	Type B Ballast Bypassed	Type B Ballast Bypassed	Type B Ballast Bypassed	Type B Ballast Bypassed	Type B Ballast Bypassed	
	Socket Wiring	Single-Ended Non-Shunted	Single-Ended Non-Shunted	Single-Ended Non-Shunted	Single-Ended Non-Shunted	Single-Ended Non-Shunted	
	Lamp Wattage (W)	9W	12W	15W	24W	33W	24W 33W

Light	Lamp Max Lumens (lm)	1,150	1,400	1,800	3,500	4,400	3,500	4,400
	CCT (K)	3000 / 3500 / 4000 / 5000	3000 / 3500 / 4000 / 5000	3000 / 3500 / 4000 / 5000	3000 / 3500 / 4000 / 5000	3000 / 3500 / 4000 / 5000		3000 / 3500 / 4000 / 5000
	Light Source	LED	LED	LED	LED	LED		LED
	Tube Length	2FT	3FT	4FT	8FT	8FT		8FT
	Beam Angle / Beam Spread	230° / 330°	230° / 330°	230° / 330°	230° / 330°	230° / 330°		230° / 330°

Physical	Tube Material	Glass with Toughened Ends	Glass with Toughened Ends	Glass with Toughened Ends	Glass with Toughened Ends	Glass with Toughened Ends	
	Length (in.)	23.7	35.75	47.72	93.74	93.74	
	Diameter (in.)	1.00	1.00	1.00	0.94	0.94	
	Width (in.)	---	---	---	---	---	
	Weight (lbs.)	0.25	0.35	0.45	0.90	0.90	

Features	DLC Listed	Yes, DLC 4.2	No Category	Yes, DLC 4.2	No Category	No Category	
	Universal Tombstone Technology	No	No	No	Not Applicable	Not Applicable	
	P.E.T. Shatter Guard Glass	Yes, Option	Yes, Option	Yes, Option	Yes, Included	Yes, Included	
	Integrated Sensors <small>* If yes, verify availability on cut sheet.</small>	Yes	Yes	Yes	Yes	Yes	



T8 (T12) LINEAR REPLACEMENT LAMPS

Type B: Double-Ended Ballast Bypassed (Quick Bypass)

[Click title for Cut Sheet and more >>](#)

Lunera T8 LED 2FT

Lunera T8 LED 3FT






Lunera T8 LED 4FT

Lunera T8 LED 8FT

Lunera T12 LED 8FT

Replaces	Equivalent Lamp Type	T8 Linear	T8 Linear	T8 Linear	T8 Linear	T12 Linear (using T8 lamp / T8 ballast)
	Equivalent Wattage	20/17/15W	30/25/21W	32/30/28/25W	75/60/59/54W	75/60/59/54W
	Socket	Bi-Pin G13	Bi-Pin G13	Bi-Pin G13	Double Recessed Contact R17d	Double Recessed Contact R17d
	Dimmable	Contact Lunera for Dimmer Compatibility	Contact Lunera for Dimmer Compatibility	Contact Lunera for Dimmer Compatibility	Contact Lunera for Dimmer Compatibility	Contact Lunera for Dimmer Compatibility

Energy	Power Source	Type B Ballast Bypassed	Type B Ballast Bypassed	Type B Ballast Bypassed	Type B Ballast Bypassed	Type B Ballast Bypassed
	Socket Wiring	Double-Ended Non-Shunted or Shunted	Double-Ended Non-Shunted or Shunted	Double-Ended Non-Shunted or Shunted	Double-Ended Non-Shunted or Shunted	Double-Ended Non-Shunted or Shunted
	Lamp Wattage (W)	9W	12W	12W / 14W	17W	43W

Light	Lamp Max Lumens (lm)	1,200	1,400	1,800	2,200	5,500	5,500	
	CCT (K)	3000 / 3500 / 4000 / 5000	3000 / 3500 / 4000 / 5000	3000 / 3500 / 4000 / 5000	3000 / 3500 / 4000 / 5000	3000 / 3500 / 4000 / 5000	3000 / 3500 / 4000 / 5000	
	Light Source	LED	LED	LED	LED	LED	LED	
	Tube Length	2FT 	3FT 	4FT 	8FT 	8FT 		
	Beam Angle / Beam Spread	230° / 330°	230° / 330°	230° / 330°	230° / 330°	230° / 330°	230° / 330°	230° / 330°

Physical	Tube Material	Glass with Toughened Ends	Glass with Toughened Ends	Glass with Toughened Ends	Glass with Toughened Ends	Glass with Toughened Ends
	Length (in.)	23.7	35.75	47.72	93.74	93.74
	Diameter (in.)	1.00	1.00	1.00	0.94	0.94
	Width (in.)	---	---	---	---	---
	Weight (lbs.)	0.25	0.35	0.45	0.90	0.90

Features	DLC Listed	Yes, DLC 4.2	No Category	Yes, DLC 4.2	No Category	No Category
	Universal Tombstone Technology	Yes	Yes	Yes	Yes	Yes
	P.E.T. Shatter Guard Glass	Yes, Option	Yes, Option	Yes, Option	Yes, Included	Yes, Included
	Integrated Sensors <small>* If yes, verify availability on cut sheet.</small>	Yes	Yes	Yes	Yes	Yes





T8 U-BEND REPLACEMENT LAMPS

Type A: Ballast Driven and Type B: Single-Ended Ballast Bypassed

[Click title for Cut Sheet and more >>](#)

Lunera T8 LED U-Bend 6" Gap

Lunera T8 LED U-Bend 1-5/8" Gap

		Lunera T8 LED U-Bend 6" Gap		Lunera T8 LED U-Bend 1-5/8" Gap	
Replaces	Equivalent Lamp Type	T8 U-Bend		T8 U-Bend	
	Equivalent Wattage	32/31/29/28/25W		32/31/29/28/25W	
	Socket	Bi-Pin G13		Bi-Pin G13	
	Dimmable	Contact Lunera for Dimmer Compatibility		Contact Lunera for Dimmer Compatibility	
Energy	Power Source	Type A: Ballast Driven (Instant/Rapid/Programmed)		Type B Ballast Bypassed	
	Socket Wiring	Shunted or Un-Shunted Tombstone		Single-Ended Non-Shunted	
	Lamp Wattage (W)	12W	15W / 17W	15W	18W
Light	Lamp Max Lumens (lm)	1,800	2,200	1,800	2,200
	CCT (K)	3000 / 3500 / 4000 / 5000		3000 / 3500 / 4000 / 5000	
	Light Source	LED		LED	
	Tube Length	22in		22in	
					
	Beam Angle / Beam Spread	230° / 330°		230° / 330°	
Physical	Tube Material	Glass with Toughened Ends		Glass with Toughened Ends	
	Tube Gap	6in		1-5/8in.	
	Length (in.)	22.40		22.40	
	Diameter (in.)	0.97		0.97	
	Width (in.)	6.00		1.61	
	Weight (lbs.)	0.50		0.50	
Features	DLC Listed	DLC 4.2		Yes, DLC 4.2	
	Universal Tombstone Technology	No		No	
	Thermal Fuse Protection	Yes		No	
	P.E.T. Shatter Guard Glass	No		No	
	Integrated Sensors <small>* If yes, verify availability on cut sheet.</small>	Yes		Yes	

T5HO (T5) REPLACEMENT LAMPS

Type A: Ballast Driven

[Click title for Cut Sheet and more >>](#)

Lunera T5HO 2FT

Lunera T5HO 4FT

Lunera T5HO 4FT (Gen 1)

		Lunera T5HO 2FT	Lunera T5HO 4FT	Lunera T5HO 4FT (Gen 1)	Lunera T5HO 4FT (Gen 1)	
Replaces	Equivalent Lamp Type	T5HO Linear	T5HO Linear	T5 Linear (using T5HO lamp/T5 Ballast)	T5HO Linear	T5 Linear (using T5HO lamp/T5 Ballast)
	Equivalent Wattage	22W	54W	28W	54W	28W
	Socket	Mini Bi-Pin G5	Mini Bi-Pin G5	Mini Bi-Pin G5	Mini Bi-Pin G5	Mini Bi-Pin G5
	Dimmable	Contact Lunera for Dimmer Compatibility	Contact Lunera for Dimmer Compatibility	Contact Lunera for Dimmer Compatibility	Contact Lunera for Dimmer Compatibility	Contact Lunera for Dimmer Compatibility
Energy	Power Source	Type A: T5HO Ballast Driven (Instant/Rapid/Programmed)	Type A: T5HO Ballast Driven (Instant/Rapid/Programmed)	Type A: T5 Ballast Driven (Instant/Rapid/Programmed)	Type A: T5HO Ballast Driven (Instant/Rapid/Programmed)	Type A: T5 Ballast Driven (Instant/Rapid/Programmed)
	Socket Wiring	Shunted or Un-Shunted	Shunted or Un-Shunted	Shunted or Un-Shunted	Shunted or Un-Shunted	Shunted or Un-Shunted
	Lamp Wattage (W)	11W	25W	11W	25W	11W
Light	Lamp Max Lumens (lm)	1,400	3,500	1,300	3,200	1,300
	CCT (K)	3000 / 3500 / 4000 / 5000	3000 / 3500 / 4000 / 5000	3000 / 3500 / 4000 / 5000	3000 / 3500 / 4000 / 5000	3000 / 3500 / 4000 / 5000
	Light Source	LED	LED	LED	LED	LED
	Tube Length	2FT	4FT	4FT	4FT	4FT
	Beam Angle / Beam Spread	230° / 330°	230° / 330°	230° / 330°	230° / 330°	230° / 330°
Physical	Tube Material	Glass with Toughened Ends	Glass with Toughened Ends	Glass with Toughened Ends	Glass with Toughened Ends	Glass with Toughened Ends
	Tube Gap	---	---	---	---	---
	Length (in.)	23.79	45.80	45.80	45.80	45.80
	Diameter (in.)	0.62	0.62	0.62	0.62	0.62
	Width (in.)	---	---	---	---	---
	Weight (lbs.)	0.25	0.25	0.25	0.25	0.25
Features	DLC Listed	No	Yes, DLC 4.2	Yes, DLC 4.2	No	No
	Overdrive Protection	Yes	Yes	Yes	Yes	Yes
	P.E.T. Shatter Guard Glass	No	No	No	No	No
	Integrated Sensors <small>* If yes, verify availability on cut sheet.</small>	No	No	No	No	No

T8 and T5HO LINEAR RETROFIT KITS

Type C: External Driver

[Click title for Cut Sheet and more >>](#)

Lunera T8 4FT
4-Lamps + Driver

Lunera T8 4FT
2-Lamps + Driver






Lunera T8 2FT
4-Lamps + Driver

Lunera T8 2FT
2-Lamps + Driver

Lunera T5HO 4FT
2-Lamps + Driver

Replaces	Equivalent Lamp Type	T8 Linear (x4)		T8 Linear (x2)		T8 Linear (x4)		T8 Linear (x2)		T5HO Linear (x2)	
	Equivalent Wattage Replaced	128W		64W		88W		44W		108W	
	Socket	Bi-Pin G13		Bi-Pin G13		Bi-Pin G13		Bi-Pin G13		Mini Bi-Pin G5	
	Dimmable	Yes, 0-10V		Yes, 0-10V		Yes, 0-10V		Yes, 0-10V		Yes, 0-10V	

Energy	Power Source	Dimmable External LED Driver		Dimmable External LED Driver		Dimmable External LED Driver		Dimmable External LED Driver		Dimmable External LED Driver	
	Socket Wiring	Shunted or Un-Shunted		Shunted or Un-Shunted		Shunted or Un-Shunted		Shunted or Un-Shunted		Shunted or Un-Shunted	
	Kit Lamp Wattage (W)	48W	60W	24W	30W	32W		16W		50W	

Light	Kit Lamp Max Lumens (lm)	7,200	8,800	4,400	3,600	4,800		2,400		7,000	
	CCT (K)	3000 / 3500 / 4000 / 5000		3000 / 3500 / 4000 / 5000		3000 / 3500 / 4000 / 5000		3000 / 3500 / 4000 / 5000		3000 / 3500 / 4000 / 5000	
	Light Source	LED		LED		LED		LED		LED	
	Tube Length	4FT 		4FT 		2FT 		2FT 		4FT 	
	Beam Angle / Beam Spread	180° / 330°		180° / 330°		180° / 330°		180° / 330°		180° / 330°	

Physical	Tube Material	Glass with Toughened Ends		Glass with Toughened Ends		Glass with Toughened Ends		Glass with Toughened Ends		Glass with Toughened Ends	
	Tube Gap	---		---		---		---		---	
	Length (in.)	23.79		45.80		45.80		45.80		45.80	
	Diameter (in.)	0.62		0.62		0.62		0.62		0.62	
	Width (in.)	---		---		---		---		---	
	Weight (lbs.)	0.25		0.25		0.25		0.25		0.25	

Features	DLC Listed	Yes, DLC 4.2 (Pending)		Yes, DLC 4.2		Yes, DLC 4.2 (Pending)		Yes, DLC 4.2		Yes, DLC 4.2	
	P.E.T. Shatter Guard Glass	No		No		No		No		No	
	Integrated Sensors	No		No		No		No		No	

METAL HALIDE / HIGH PRESSURE SODIUM REPLACEMENT LAMPS - VERTICAL

Type A: Ballast Driven







LUNERA®

[<< BACK TO TOP](#)

[Click title for Cut Sheet and more >>](#)

Lunera HID Vertical - Mogul E39

Lunera HID Vertical - Medium E26

Replaces	Equivalent Lamp Type	Metal Halide or High Pressure Sodium	Metal Halide or High Pressure Sodium	Metal Halide or High Pressure Sodium	Metal Halide or High Pressure Sodium	Metal Halide or High Pressure Sodium	Metal Halide or High Pressure Sodium
	Equivalent Wattage	400W	400/320/310/250W	250/175/150/100/70W	175/150/100/70W	250/175/150/100/70W	175/150/100/70W
	Socket	Mogul E39	Mogul E39	Mogul E39	Mogul E39	Medium E26	Medium E26
	Dimmable	Contact Lunera for Dimmer Compatibility	Contact Lunera for Dimmer Compatibility	Contact Lunera for Dimmer Compatibility	Contact Lunera for Dimmer Compatibility	Contact Lunera for Dimmer Compatibility	Contact Lunera for Dimmer Compatibility
Energy	Power Source	Type A CWA Ballast Driven	Type A CWA Ballast Driven	Type A CWA Ballast Driven	Type A CWA Ballast Driven	Type A CWA Ballast Driven	Type A CWA Ballast Driven
	CWA Ballast Types	M59 / S51	M59 / M132 / M58 S51 / S67 / S50	M58 / M57 / M102 / M90 / M98 S50 / S60 / S55 / S54 / S62	M57 / M102 / M90 / M98 S50 / S60 / S55 / S54 / S62	M57 / M102 / M90 / M98 S50 / S60 / S55 / S54 / S62	M57 / M102 / M90 / M98 S50 / S60 / S55 / S54 / S62
	Lamp Wattage (W)	207W	164W	95W	54W	95W	54W
Light	Lamp Max Lumens (lm)	21,300	17,900	9,900	5,700	9,900	5,700
	CCT (K)	3500 / 4000 / 5000	3500 / 4000 / 5000	3500 / 4000 / 5000	3500 / 4000 / 5000	3500 / 4000 / 5000	3500 / 4000 / 5000
	Light Source	LED	LED	LED	LED	LED	LED
	Lamp Mount / Light Direction	Vertical 	Vertical 	Vertical 	Vertical 	Vertical 	Vertical 
Physical	Lens Type	Clear	Clear	Frosted	Frosted	Frosted	Frosted
	Type V Lens Option	No	No	No	No	Yes	Yes
	10% Uplight Option	No	No	Yes	Yes	Yes	Yes
	Short Neck Length Option*	No	No	No	No	Yes	Yes
	Length (in.)	9.88	9.88	8.59	8.59	8.18 or 5.01*	8.18 or 5.01*
	Diameter (in.)	6.31	6.31	6.31	6.31	6.31	6.31
	Weight (lbs.)	1.90	1.90	1.80	1.80	1.80 or 1.50*	1.80 or 1.50*
Features	DLC Listed	No Category	No Category	No Category	No Category	No Category	No Category
	Fixture Retrofit Kit	No	No	No	No	No	No
	Integrated Sensors	No	No	No	No	No	No

METAL HALIDE / HIGH PRESSURE SODIUM REPLACEMENT LAMPS - VERTICAL

Type B: Ballast Bypassed







LUNERA®

[<< BACK TO TOP](#)

[Click title for Cut Sheet and more >>](#)

Lunera HID Vertical - Mogul E39

Lunera HID Vertical - Medium E26

Replaces	Equivalent Lamp Type	Metal Halide or High Pressure Sodium	Metal Halide or High Pressure Sodium	Metal Halide or High Pressure Sodium	Metal Halide or High Pressure Sodium	Metal Halide or High Pressure Sodium	Metal Halide or High Pressure Sodium
	Equivalent Wattage	400W	400/320/310/250W	250/175/150/100/70W	175/150/100/70W	250/175/150/100/70W	175/150/100/70W
	Socket	Mogul E39	Mogul E39	Mogul E39	Mogul E39	Medium E26	Medium E26
	Dimmable	Contact Lunera for Dimmer Compatibility	Contact Lunera for Dimmer Compatibility	Contact Lunera for Dimmer Compatibility	Contact Lunera for Dimmer Compatibility	Contact Lunera for Dimmer Compatibility	Contact Lunera for Dimmer Compatibility
Energy	Power Source	Type B Ballast Bypassed	Type B Ballast Bypassed	Type B Ballast Bypassed	Type B Ballast Bypassed	Type B Ballast Bypassed	Type B Ballast Bypassed
	CWA Ballast Types	M59 / S51	M59 / M132 / M58 S51 / S67 / S50	M58 / M57 / M102 / M90 / M98 S50 / S60 / S55 / S54 / S62	M57 / M102 / M90 / M98 S50 / S60 / S55 / S54 / S62	M57 / M102 / M90 / M98 S50 / S60 / S55 / S54 / S62	M57 / M102 / M90 / M98 S50 / S60 / S55 / S54 / S62
	Lamp Wattage (W)	207W	164W	95W	54W	95W	54W
Light	Lamp Max Lumens (lm)	21,300	17,900	9,900	5,700	9,900	5,700
	CCT (K)	3500 / 4000 / 5000	3500 / 4000 / 5000	3500 / 4000 / 5000	3500 / 4000 / 5000	3500 / 4000 / 5000	3500 / 4000 / 5000
	Light Source	LED	LED	LED	LED	LED	LED
	Lamp Mount / Light Direction	Vertical 	Vertical 	Vertical 	Vertical 	Vertical 	Vertical 
Physical	Lens Type	Clear	Clear	Frosted	Frosted	Frosted	Frosted
	Type V Lens Option	No	No	No	No	Yes	Yes
	10% Uplight Option	No	No	Yes	Yes	Yes	Yes
	Short Neck Length Option*	No	No	No	No	Yes	Yes
	Length (in.)	9.88	9.88	8.59	8.59	8.18 or 5.01*	8.18 or 5.01*
	Diameter (in.)	6.31	6.31	6.31	6.31	6.31	6.31
	Weight (lbs.)	1.90	1.90	1.80	1.80	1.80 or 1.50*	1.80 or 1.50*
Features	DLC Listed	Yes, 4.2	Yes, 4.2	Yes, 4.2	Yes, 4.2	No Category	No Category
	Fixture Retrofit Kit	Yes (Hardwired Attachment Ring)	Yes (Hardwired Attachment Ring)	Yes (Hardwired Attachment Ring)	No	No	No
	Integrated Sensors	Yes	Yes	Yes	Yes	Yes	Yes



METAL HALIDE / HIGH PRESSURE SODIUM REPLACEMENT LAMPS - VERTICAL (NO COOLING FAN)

Type A: Ballast Driven

[Click title for Cut Sheet and more >>](#)

Lunera MH Vertical - No Cooling Fan

Lunera HPS Vertical - No Cooling Fan

Replaces	Equivalent Lamp Type	Metal Halide				High Pressure Sodium			
	Equivalent Wattage	400W	320W	250W	175W	400W	310W	250W	200W
	Socket	Mogul E39				Mogul E39			
	Dimmable	Contact Lunera for Dimmer Compatibility				Contact Lunera for Dimmer Compatibility			
Energy	Power Source	Type A: MH CWA Ballast Driven				Type A: HPS CWA Ballast Driven			
	CWA Ballast Types	M59	M132	M58	M57	S51	S67	S66	S50
	Lamp Wattage (W)	145W	130W	91W	82W	160W	140W	110W	90W
Light	Lamp Max Lumens (lm)	16,300	14,000	10,500	9,100	15,000	13,100	11,500	9,100
	CCT (K)	3500 / 4000 / 5000				3500 / 4000 / 5000			
	Light Source	LED				LED			
	Lamp Mount / Light Direction	Vertical				Vertical			
									
Physical	Lens Type	Clear				Clear			
	Length (in.)	9.41				9.41			
	Diameter (in.)	8.27				8.23			
	Weight (lbs.)	3.75				3.75			
Features	DLC Listed	No Category				No Category			
	Thermal IQ Technology	Yes				Yes			
	Fixture Retrofit Kit	No				No			
	Integrated Sensors	No				No			

METAL HALIDE / HIGH PRESSURE SODIUM REPLACEMENT LAMPS - HORIZONTAL

Type A: Ballast Driven

[Click title for Cut Sheet and more >>](#)

Lunera MH Horizontal

Lunera HPS Horizontal

Replaces	Equivalent Lamp Type	Metal Halide				High Pressure Sodium			
	Equivalent Wattage	400W	320W	250W	175W	400W	310W	250W	200W
	Socket	Mogul E39				Mogul E39			
	Dimmable	Contact Lunera for Dimmer Compatibility				Contact Lunera for Dimmer Compatibility			
Energy	Power Source	Type A: MH CWA Ballast Driven				Type A: HPS CWA Ballast Driven			
	CWA Ballast Types	M59	M132	M58	M57	S51	S67	S66	S50
	Lamp Wattage (W)	145W	130W	92W	82W	118W	105W	83W	63W
Light	Lamp Max Lumens (lm)	14,800	12,800	9,200	7,900	10,800	9,700	8,500	6,500
	CCT (K)	3500 / 4000 / 5000		3500 / 4000 / 5000		3500 / 4000 / 5000		3500 / 4000 / 5000	
	Light Source	LED				LED			
	Lamp Mount / Light Direction	Horizontal				Horizontal			
Physical	Lens Type	Clear				Clear			
	Length (in.)	9.40				9.40			
	Diameter (in.)	4.20				4.20			
	Weight (lbs.)	2.50				2.50			
Features	DLC Listed	No Category				No Category			
	Fixture Retrofit Kit	No				No			
	Integrated Sensors	No				No			



METAL HALIDE / HIGH PRESSURE SODIUM REPLACEMENT LAMPS - 360 DEGREE POST TOP





Type A: Ballast Driven and Type B: Ballast Bypassed

[<< BACK TO TOP](#)

[Click title for Cut Sheet and more >>](#)

Lunera HID 360 - 8K

Lunera HID 360 - 5K




Replaces	Equivalent Lamp Type	Metal Halide or High Pressure Sodium		Metal Halide or High Pressure Sodium		Metal Halide or High Pressure Sodium		Metal Halide or High Pressure Sodium	
	Equivalent Wattage	250/175/150W		250/175/150W		175/150/100/70/50W		175/150/100/70/50W	
	Socket	Mogul E39 or Medium E26		Mogul E39 or Medium E26		Mogul E39 or Medium E26		Mogul E39 or Medium E26	
	Dimmable	Contact Lunera for Dimmer Compatibility		Contact Lunera for Dimmer Compatibility		Contact Lunera for Dimmer Compatibility		Contact Lunera for Dimmer Compatibility	
Energy	Power Source	Type A: CWA Ballast Driven		Type B: Ballast Bypassed		Type A: CWA Ballast Driven		Type B: Ballast Bypassed	
	CWA Ballast Types	M58 / M57 / M102 S50 / S60 / S55		Not Applicable		M57 / M102 / M90 / M98 S60 / S55 / S54 / S62		Not Applicable	
	Lamp Wattage (W)	90W		90W		53W		53W	
Light	Lamp Max Lumens (lm)	8,600	6,000	8,600	6,000	5,700	3,500	5,700	3,500
	CCT (K)	3500K 4000K 5000K	2000K	3500K 4000K 5000K	2000K	3500K 4000K 5000K	2000K	3500K 4000K 5000K	2000K
	Light Source	LED		LED		LED		LED	
	Lamp Mount / Light Direction	360 Degrees 		360 Degrees 		360 Degrees 		360 Degrees 	
Physical	Lens Type	Frosted		Frosted		Frosted		Frosted	
	Length (in.)	8.19		8.19		8.19		8.19	
	Diameter (in.)	4.36		4.36		4.36		4.36	
	Weight (lbs.)	2.00		2.00		2.00		2.00	
Features	DLC Listed	No Category	Yes, DLC 4.2 (E39 Mogul Only)	No Category	No Category	No Category	No Category	No Category	No Category
	Fixture Retrofit Kit	No	No	No	No	No	No	No	No
	Integrated Sensors	No	No	No	No	No	No	No	No


METAL HALIDE / HIGH PRESSURE SODIUM RETROFIT KITS - VERTICAL

Type B: Ballast Bypassed and Hardwired Directly to Line Voltage (mogul socket removed)

[Click title for Cut Sheet and more >>](#)

Lunera HID Vertical - Hardwired Clasp replaces Mogul E39

Replaces	Equivalent Lamp Type	Metal Halide or High Pressure Sodium	Metal Halide or High Pressure Sodium	Metal Halide or High Pressure Sodium
	Equivalent Wattage	400W	400/320/310/250W	250/175/150/100/70W
	Socket	Hardwired to Line. Mounting Clasp Replaces E39	Hardwired to Line. Mounting Clasp Replaces E39	Hardwired to Line. Mounting Clasp Replaces E39
	Dimmable	Contact Lunera for Dimmer Compatibility	Contact Lunera for Dimmer Compatibility	Contact Lunera for Dimmer Compatibility
Energy	Power Source	Type B: Ballast Bypassed	Type B: Ballast Bypassed	Type B: Ballast Bypassed
	Lamp Wattage (W)	207W	164W	95W
Light	Light Source	LED	LED	LED
	Lamp Mount / Light Direction	Vertical 	Vertical 	Vertical 
	Lamp Max Lumens (lm)	21,300	17,900	9,900
	CCT (K)	3500 / 4000 / 5000	3500 / 4000 / 5000	3500 / 4000 / 5000
Physical	Lens Type	Clear	Clear	Frosted
	Length (in.)	9.88	9.88	8.59
	Diameter (in.)	6.31	6.31	6.31
	Weight (lbs.)	1.90	1.90	1.90
Features	DLC Listed	Yes, DLC 4.2	Yes, DLC 4.2	Yes, DLC 4.2
	Fixture Retrofit Kit	Yes	Yes	Yes
	Integrated Sensors <small>* If yes, verify availability on cut sheet.</small>	No	No	No



The Mogul E39 socket is removed from the fixture.

The ballast is bypassed or removed, hardwiring the LED lamp directly to 120V ~ 277V line voltage.

A slotted ring clasp is attached to the fixture's reflector, replacing the E39 socket, and the lamp is secured to the clasp.

The fixture has been retrofitted as an LED fixture.